



Usersnap Limit IPs for Widget Documentation

To limit the IP addresses where the Usersnap widget will appear, use the following sample code:

```
<!DOCTYPE html>
<html>
<head>
<meta http-equiv="Content-Type" content="text/html; charset=UTF-8">
<script src="https://ajax.googleapis.com/ajax/libs/jquery/2.2.2/jquery.min.js"></script>
<title>Test Ip Allow</title>
<script type="text/javascript">
function _isUsersnapAllowed(cb) {
    //add multiple ip addresses here
    var ipList = ['XX.XX.XX.XX'];
    $.getJSON('//jsonip.com/', function(data) {
        for(var i = 0; i < ipList.length; i++) {
            if (ipList[i] === data.ip) {
                cb.call(window, true);
                return true;
            }
        }
        cb.call(window, false);
        return false;
    });
}

(function() {
    _isUsersnapAllowed(function(result) {
        //returns true or false
        if (result) {
            var s = document.createElement("script");
            s.type = "text/javascript";
            s.async = true;
            s.src = '//api.usersnap.com/load/'+
                '[your-api-key-here].js';
        }
    });
})();

```

```
    var x = document.getElementsByTagName('script')[0];
    x.parentNode.insertBefore(s, x);
  }
});
})();
</script>
</head>
<body>
  <h1>This is a IP test page</h1>
</body>
</html>
```